

Geodesic-based manifold learning for parameterization of triangular meshes

International Journal on Interactive Design and Manufacturing (IJIDeM)
pp 1–14

Authors Authors and affiliations

Diego A. Acosta, Oscar E. Ruiz, Santiago Arroyave, Roberto Ebratt, Carlos Cadavid ,
Juan J. Londono

Original Paper

First Online: 19 October 2014

DOI (Digital Object Identifier): [10.1007/s12008-014-0249-9](https://doi.org/10.1007/s12008-014-0249-9)

Cite this article as:

Acosta, D.A., Ruiz, O.E., Arroyave, S. et al. Int J Interact Des Manuf (2014).
[doi:10.1007/s12008-014-0249-9](https://doi.org/10.1007/s12008-014-0249-9)

117

Views

Abstract

Reverse Engineering (RE) requires representing with free forms (NURBS, Spline, Bézier) a real surface S_0 which has been point-sampled. To serve this purpose, we have implemented an algorithm that minimizes the accumulated distance between the free form and the (noisy) point sample. We use a dual-distance calculation point to / from surfaces, which discourages the forming of outliers and artifacts. This algorithm seeks a minimum in a function f that represents the fitting error, by using as tuning variable the control polyhedron for the free form. The topology (rows, columns) and geometry of the control polyhedron are determined by alternative geodesic-based dimensionality reduction methods: (a) graph-approximated geodesics (Isomap), or (b) PL orthogonal geodesic grids. We assume the existence of a triangular mesh of the point sample (a reasonable expectation in current RE). A bijective composition mapping $S_0 \subset \mathbb{R}^3 \longleftrightarrow \mathbb{R}^2$ allows to estimate a size of the control polyhedrons favorable to uniform-speed parameterizations. Our results show that orthogonal geodesic grids is a direct and intuitive

parameterization method, which requires more exploration for irregular triangle meshes. Isomap gives a usable initial parameterization whenever the graph approximation of geodesics on S_0 be faithful. These initial guesses, in turn, produce efficient free form optimization processes with minimal errors. Future work is required in further exploiting the usual triangular mesh underlying the point sample for (a) enhancing the segmentation of the point set into faces, and (b) using a more accurate approximation of the geodesic distances within S_0 , which would benefit its dimensionality reduction.

Keywords

Computational geometry Parametric surfaces Surface reconstruction Reverse engineering

Abbreviations

PL

Piecewise linear

B

Solid object in \mathbb{R}^3 . $B \subset \mathbb{R}^3$ is the closure of a bounded and connected open set, whose border ∂B is a 2-dimensional manifold.

S_0

Freeform parametric surface on which a Face of ∂B is mounted

P

$\{p_0, p_1, \dots\}$ Unordered point sample of S_0

$S(u, v)$

Parametric surface, which fits the set **P**, so $S \approx S_0$

u, v

Surface parameters

$N_{i,p}, N_{j,q}$

B-spline base functions $\mathbb{R} \rightarrow \mathbb{R}$,

n, m

Number of control points of S in u, v directions respectively

Cp

Control polyhedron for S

k

Norm degree. $|(x_1, x_2, \dots, x_n)|_k = \sqrt[k]{\sum_{i=1}^n |x_i|^k}$

f

Function minimized when fitting S to **P**

d_i

Minimum distance between the i -th point p_i of **P** and S

LM

Levenberg-Marquardt

RE

Reverse engineering

Gr Regular, axis-aligned vertex grid in \mathbb{R}^2  G Graph (\mathbf{P}, E) with vertex set \mathbf{P} and edge set E , nearly embedded in S_0 D Square matrix in which $D(i, j) = \text{dist}(p_i, p_j)$, with $\text{dist}()$ approaching the geodesic distance on S_0 between sample points p_i and p_j T $\{t_1, t_2, \dots\}$ Triangular mesh of triangles t_i with vertices in \mathbf{P} B_{UV} Parametric rectangular connected subset of \mathbb{R}^2  c_G PL geodesic curve on T

References

1. Nyquist, H.: Certain topics in telegraph transmission theory. *Trans. Am. Inst. Electr. Eng.* **47**(2), 617–644 (1928)
[CrossRef](http://dx.doi.org/10.1109/T-AIEE.1928.5055024) (<http://dx.doi.org/10.1109/T-AIEE.1928.5055024>).
2. Shannon, C.: Communication in the presence of noise. *Proc. IRE* **37**(1), 10–21 (1949)
[MathSciNet](http://www.ams.org/mathscinet-getitem?mr=28549) (<http://www.ams.org/mathscinet-getitem?mr=28549>)
[CrossRef](http://dx.doi.org/10.1109/JRPROC.1949.232969) (<http://dx.doi.org/10.1109/JRPROC.1949.232969>).
3. Varady, T., Martin, R., Cox, J.: Reverse engineering of geometric modeling—an introduction. *Comput. Aided Des.* **29**(4), 255–268 (1997)
[CrossRef](http://dx.doi.org/10.1016/S0010-4485(96)00054-1) ([http://dx.doi.org/10.1016/S0010-4485\(96\)00054-1](http://dx.doi.org/10.1016/S0010-4485(96)00054-1)).
4. Cheng, K., Wang, W., Qin, H., Wong, K., Yang, H., Liu, Y.: Design and analysis of optimization methods for subdivision surface fitting. *IEEE Trans. Vis. Comput. Graph.* **13**(5), 878–890 (2007)
[CrossRef](http://dx.doi.org/10.1109/TVCG.2007.1064) (<http://dx.doi.org/10.1109/TVCG.2007.1064>).
5. Vieira, M., Shimada, K.: Surface mesh segmentation and smooth surface extraction through region growing. *Comput. Aided Geom. Des.* **22**(8), 771–792 (2005)
[MathSciNet](http://www.ams.org/mathscinet-getitem?mr=2173577) (<http://www.ams.org/mathscinet-getitem?mr=2173577>)
[CrossRef](http://dx.doi.org/10.1016/j.cagd.2005.03.006) (<http://dx.doi.org/10.1016/j.cagd.2005.03.006>)
[MATH](http://www.emis.de/MATH-item?1119.65316) (<http://www.emis.de/MATH-item?1119.65316>)
6. Shamir, A.: A survey on mesh segmentation techniques. *Comput. Graph. Forum* **27**(6), 1539–1556 (2008). doi:10.1111/j.1467-8659.2007.01103.x
(<http://dx.doi.org/10.1111/j.1467-8659.2007.01103.x>)
[CrossRef](http://dx.doi.org/10.1111/j.1467-8659.2007.01103.x) (<http://dx.doi.org/10.1111/j.1467-8659.2007.01103.x>)
[MATH](http://www.emis.de/MATH-item?1162.68769) (<http://www.emis.de/MATH-item?1162.68769>)
7. Liu, R., Zhang, H.: Mesh segmentation via spectral embedding and contour analysis. In: *EuroGraphics*, 3 (2007)
8. Ji, Z., Liu, L., Chen, Z., Wang, G.: Easy mesh cutting. *Comput. Graph. Forum* **25**(3), 283–291 (2006). doi:10.1111/j.1467-8659.2006.00947.x
(<http://dx.doi.org/10.1111/j.1467-8659.2006.00947.x>)

CrossRef (<http://dx.doi.org/10.1111/j.1467-8659.2006.00947.x>).

9. Lee, Y., Lee, S., Shamir, A., Cohen-Or, D., Seidel, H.P.: Mesh scissoring with minima rule and part salience. *Comput. Aided Geom. Des.* **22**(5), 444–465 (2005). doi:[10.1016/j.cagd.2005.04.002](https://doi.org/10.1016/j.cagd.2005.04.002) (<http://dx.doi.org/10.1016/j.cagd.2005.04.002>)
CrossRef (<http://dx.doi.org/10.1016/j.cagd.2005.04.002>)
MATH (<http://www.emis.de/MATH-item?1205.65120>)
10. Orozco, M. et al. : Geometry and topology-based segmentation of 2-manifold triangular meshes in r^3 . Master's thesis, Universidade de Vigo, Spain (2014)
11. Klein, R., Schilling, A., Straßer, W.: Reconstruction and simplification of surfaces from contours. In: *Computer Graphics and Applications, 1999. Proceedings. Seventh Pacific Conference on*, pp. 198–207. IEEE (1999)
12. Ruiz, O., Cadavid, C., Granados, M., Pena, S., Vásquez, E.: 2d shape similarity as a complement for voronoi-delaunay methods in shape reconstruction. *Comput. Graph.* **29**(1), 81–94 (2005)
CrossRef (<http://dx.doi.org/10.1016/j.cag.2004.11.009>)
13. Braquelaire, A., Kerautret, B.: Reconstruction of lambertian surfaces by discrete equal height contours and regions propagation. *Image Vis. Comput.* **23**(2), 177–189 (2005)
CrossRef (<http://dx.doi.org/10.1016/j.imavis.2004.06.006>)
14. Piegl, L., Tiller, W.: Parametrization for surface fitting in reverse engineering. *Comput. Aided Des.* **33**(8), 593–603 (2001)
CrossRef ([http://dx.doi.org/10.1016/S0010-4485\(00\)00103-2](http://dx.doi.org/10.1016/S0010-4485(00)00103-2))
15. Brujic, D., Ainsworth, I., Ristic, M.: Fast and accurate nurbs fitting for reverse engineering. *Int. J. Adv. Manuf. Technol.* **54**(5), 691–700 (2011)
CrossRef (<http://dx.doi.org/10.1007/s00170-010-2947-1>)
16. Zhang, S. et al. : Multi-resolution mesh fitting by b-spline surfaces for reverse engineering. In: *Computer-Aided Design and Computer Graphics (CAD/Graphics), 2011 12th International Conference on*, pp. 251–257. IEEE (2011)
17. Louhichi, B., Aifaoui, N., Hamdi, M., BenAmara, A., Francois, V.: An optimization-based computational method for surface fitting to update the geometric information of an existing b-rep cad model. *Int. J. CAD/CAM* **9**(1), 17–24 (2009)
18. Zhou, K., Synder, J., et al.: Iso-charts: stretch-driven mesh parameterization using spectral analysis. In: *Proceedings of the 2004 Eurographics/ACM SIGGRAPH symposium on Geometry processing*, pp. 45–54. ACM (2004)
19. Azariadis, P.N.: Parameterization of clouds of unorganized points using dynamic base surfaces. *Comput. Aided Des.* **36**(7), 607–623 (2004). doi:[10.1016/S0010-4485\(03\)00138-6](https://doi.org/10.1016/S0010-4485(03)00138-6) ([http://dx.doi.org/10.1016/S0010-4485\(03\)00138-6](http://dx.doi.org/10.1016/S0010-4485(03)00138-6))
CrossRef ([http://dx.doi.org/10.1016/S0010-4485\(03\)00138-6](http://dx.doi.org/10.1016/S0010-4485(03)00138-6))
20. Kineri, Y., Wang, M., Lin, H., Maekawa, T.: B-spline surface fitting by iterative geometric interpolation/approximation algorithms. *Comput. Aided Des.* **44**(7), 697–708 (2012). doi:[10.1016/j.cad.2012.02.011](https://doi.org/10.1016/j.cad.2012.02.011) (<http://dx.doi.org/10.1016/j.cad.2012.02.011>). ISSN 0010-4485

21. Park, C., Min, C., Kang, M.: Surface reconstruction from scattered point data on octree. *J. Korean Soc. Ind. Appl. Math.* **16**(1), 31–49 (2012). (ISSN / CODEN - 1226–9433 / KSIAM)
[MathSciNet](http://www.ams.org/mathscinet-getitem?mr=2910343) (<http://www.ams.org/mathscinet-getitem?mr=2910343>)
[CrossRef](http://dx.doi.org/10.12941/jksiam.2012.16.1.031) (<http://dx.doi.org/10.12941/jksiam.2012.16.1.031>)
22. Ruiz, O. et al. : Sensitivity analysis of optimized curve fitting to uniform-noise point samples. In: *Proceedings of the 9th International Symposium on Tools and Methods of Competitive Engineering, TMCE 2012, Karlsruhe, Germany (2012)*
23. Xiong, Y., Li, G., Mao, A.: Convergence analysis for B-spline geometric interpolation. *Comput. Graph* **36**(7), 884–891 (2012). doi:[10.1016/j.cag.2012.07.002](https://doi.org/10.1016/j.cag.2012.07.002)
(<http://dx.doi.org/10.1016/j.cag.2012.07.002>)
24. Leal, N., Leal, E., Branch, J.: Automatic construction of nurbs surfaces from unorganized points. *Dyna* **78**(166), 133–141 (2011). (ISSN 0012–7353)
25. Galvez, A., Iglesias, A., Puig-Pey, J.: Iterative two-step genetic-algorithm-based method for efficient polynomial b-spline surface reconstruction. *Inf. Sci.* **182**(1), 56–76 (2012). doi:[10.1016/j.ins.2010.09.031](https://doi.org/10.1016/j.ins.2010.09.031).ISSN0020-0255
(<http://dx.doi.org/10.1016/j.ins.2010.09.031>.ISSN0020-0255)
26. Galvez, A., Iglesias, A.: Particle swarm optimization for non-uniform rational b-spline surface reconstruction from clouds of 3d data points. *Inf. Sci.* **192**, 174–192 (2012). doi:[10.1016/j.ins.2010.11.007](https://doi.org/10.1016/j.ins.2010.11.007).ISSN0020-0255
(<http://dx.doi.org/10.1016/j.ins.2010.11.007>.ISSN0020-0255)
27. Ren, M., Cheung, C., Kong, L.: A robust surface fitting and reconstruction algorithm for form characterization of ultra-precision freeform surfaces. *Measurement* **44**(10), 2068–2077 (2011). doi:[10.1016/j.measurement.2011.08.011](https://doi.org/10.1016/j.measurement.2011.08.011)
(<http://dx.doi.org/10.1016/j.measurement.2011.08.011>)
[CrossRef](http://dx.doi.org/10.1016/j.measurement.2011.08.011) (<http://dx.doi.org/10.1016/j.measurement.2011.08.011>)
28. Wang, W., Pottmann, H., Liu, Y.: Fitting b-spline curves to point clouds by curvature-based squared distance minimization. *ACM Trans. Grap.* **25**(2), 214–238 (2006)
[CrossRef](http://dx.doi.org/10.1145/1138450.1138453) (<http://dx.doi.org/10.1145/1138450.1138453>)
29. Wagner, T. et al.: On the design of optimisers for surface reconstruction. In: *Proceedings of the 9th annual conference on Genetic and evolutionary computation*, pp. 2195–2202. ACM (2007)
30. Levenberg, K.: A method for the solution of certain non-linear problems in least squares. *Quarterly J. Appl. Math.* **II**(2), 164–168 (1944)
31. Marquardt, D.: An algorithm for least-squares estimation of nonlinear parameters. *J. Soc. Ind. Appl. Math.* **11**(2), 431–441 (1963)
[MathSciNet](http://www.ams.org/mathscinet-getitem?mr=153071) (<http://www.ams.org/mathscinet-getitem?mr=153071>)
[CrossRef](http://dx.doi.org/10.1137/0111030) (<http://dx.doi.org/10.1137/0111030>)
[MATH](http://www.emis.de/MATH-item?0112.10505) (<http://www.emis.de/MATH-item?0112.10505>)
32. Tenenbaum, J.B., De Silva, V., Langford, J.C.: A global geometric framework for nonlinear dimensionality reduction. *Science* **290**(5500), 2319–2323 (2000). doi:[10.1126/science.290.5500.2319](https://doi.org/10.1126/science.290.5500.2319)
(<http://dx.doi.org/10.1126/science.290.5500.2319>)

[CrossRef](http://dx.doi.org/10.1126/science.290.5500.2319) (<http://dx.doi.org/10.1126/science.290.5500.2319>).

33. Cox, T.F., Cox, M.A.: Multidimensional scaling. In: Monographs on Statistics and Applied Probability, 2nd edn. Chapman and Hall (2001)
34. Ruiz, O., Arroyave, S., Acosta, D.: Fitting of analytic surfaces to noisy point clouds. Laboratorio de CAD/CAM/CAE, Universidad EAFIT, Medellin, Colombia, Tech. rep. (2013)

Copyright information

© Springer-Verlag France 2014

About this article



Print ISSN

1955-2513

Online ISSN

1955-2505

Publisher Name

Springer Paris

[About this journal](#)

[Reprints and Permissions](#)

SPRINGER NATURE

© 2016 Springer International Publishing. Part of [Springer Nature](#).

Not logged in · Not affiliated · 200.12.182.187